

JAC Stick

Face Material	
JAC® STICK 87015 – transparent	JAC® STICK 87215 – white

Face Material

Glossy, special PVC film featuring inherent adhesive properties. It sticks to smooth surfaces without any need for an adhesive.

Examples of application:

For high quality durable signs, that need to be simple to apply and easy to remove and reuse. Advertising on storefront windows, decoration, lettering with interchangeable characters, protection of delicate surfaces.

Offset-printed: with both purely oxidative drying and UV-curing inks, which are resistant to plasticiser and suitable for films

Screen-printed: with conventional (i.e. solvent-based) and UV-curing inks

For print guidance please visit our website under Downloads

“Guidelines for use” – Offset printing

Characteristics	87015	87215
Weight (g/m ²)	195	195
Weight Total Laminate (g/m ²)	410	410
Thickness (µm)	150	150
Thickness Total Laminate (µm)	470	470
Shelf life of laminate* (years)	1	1
Max. outdoor durability** (years)	1	1

* Refers to adhesion and printability when stored in original packaging in dark, dry conditions at a temperature of 22 °C ± 2 °C and a relative humidity of 50% ± 5%.

** Under normal climatic conditions as prevailing in Central Europe.

Adhesive

No need for adhesive

* Not fully resistant until adhesion reaches full strength-after at least 24 hrs

Characteristics	JAC STICK
Adhesion (FTM1) after 24h on glass (N/25mm)	0.05
Recommended minimum application temperature (°C)	>=5
Heat resistance up to 24h (°C)	+70
Resistance to cold* (°C) down to	-20

Silicone Paper

PE-coated paper

Z 250 is a PE-coated medium-weight board with excellent handling and feeding properties.

Only available with JAC® STICK

Characteristics	Z250
Weight (g/m ²)	215
Thickness (µm)	320

Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>. Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.