

Jac DECO

Face Material	
JAC Deco Silver matt (67212)	JAC Deco Silver gloss (67312)

Face Material

JAC Deco is a metallized polyester film laminated on PVC film for the production of high-quality signs. It is top-coated for optimum printability. The extreme stability of the film prevents any surface texture from showing through. JAC Deco is suitable for hot stamping and displays extraordinary dimensional stability.

Offset-printed: with both purely oxidative drying and UV-curing inks, which are resistant to plasticiser / suitable for films

Screen-printed: with conventional (i.e. solvent-based) and UV-curing inks

For print guidance please visit our website under Downloads

"5.11 Storage \printing on Digilabel"

* Refers to adhesion and printability when stored in original packaging in dark, dry conditions at a temperature of 22 °C ± 2 °C and a relative humidity of 50% ± 5%.

Characteristics	67212	67312
Weight (g/m ²)	174	174
Thickness (µm)	127	127
Tensile Strength ISO 1924/2 (N/15mm) in MD	130	135
in TD	140	135
Opacity (%)	100	
Shelf life of laminate* (years)	2	2

Adhesive

Solvent-based permanent acrylic

DURO AL 170 is a solvent-based permanent acrylic adhesive. It is distinguished by its excellent light-fastness, ageing stability and plasticizer resistance.

* Not fully resistant until adhesion reaches full strength-after at least 24 hrs

Characteristics	DURO AL 170
Adhesion (FTM1) after 24h (N/25mm) on Stainless Steel	31
Initial adhesion/tack (FTM9) on Glass (N)	20
Recommended minimum application temperature (°C)	>+10
Heat resistance up to 24h (°C)	+80
Heat resistance up to 1h (°C)	+110
Resistance to cold* (°C)	-20

Silicone Paper

2 side PE coated paper

G 160 is very sturdy, siliconized board, wood-free, matt on reverse side. Both sides are coated with polyethylene. G160 offer absolute dimensional stability and moisture resistance– not printable due to the coating.

Characteristics	G 160
Weight (g/m ²)	160
Thickness (µm)	175

Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>. Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.